

## Towing sled type Transalp BUS / 6-places

|                     |  |
|---------------------|--|
| Frame               | : steel chassis MIG welded with no-rust pre-treatment and powder-coating   |
| Towing hitch        | : 50 mm. ball-hitch coupling with additional safety-belt   |
| Loading platform    | : antiskid aluminium-plate   |
| Platform dimensions | : mm. 1236 x 2575  |
| Luggage rack        | : mm. 1236 x 450   |
| Railing height      | : mm. 150 (front and rear)   |
| Suspensions         | : link arms with progressive rubber springs  |
| Skis                | : steel made skis (2) with no-rust pre-treatment and powder-coating, equipped with HD-PE plastic skins and carbide wear-bars |
| Protections         | : dual R.O.P.S.  |
| Seats               | : removable 3+3 comfortable rubber-seats equipped with safety belts  |
| Available options   | : on request is available a kit including windshield and hard top and/or ski-rack 10-places                                  |
| Weights             | : dry weight 218 kgs. / payload 534 kgs. / gross weight vehicle rating 820 kgs.  |
| Capacities          | : 6 passengers / 534 kgs.  |

**Safety notes:** Transalp Bus 6 is designed to carry up to 6 persons. Partial loading of it must be shared between the front and the rear seats. Transalp Bus must be towed only by an Alpina snowmobile of the SHERPA or SUPERCLASS series equipped with the special ball hitch and safety strap. It is recommended to stud the snowmobile tracks to improve their grip on icy snow and also to install the emergency brake (EBS). The driver must have been trained in the specific use of the machine. Use by unexperienced people is absolutely prohibited. Operation is permitted only on groomed trails and not off-trail. The climbs and descents must be passed through the line of the maximum gradient and never transversally. The use of the Transalp Bus on trails where the slope and the snow conditions could compromise the stability and grip of the vehicle and constitute a danger for those being transported is forbidden. In this regard, it is recommended to not drive through the trails with gradients greater than 20% anyhow. Furthermore, circulation on roads open to public traffic or on ski slopes during the hours open to the public is prohibited (unless otherwise authorized). Max. speed permitted: 25 kph / 15 mph. Fasten safety belts before operating the snowmobile. It is recommended to provide insurance coverage for any damage that may be caused to driver and passengers, third parties and third party property (TPL).





## Towing sled type Transalp BUS / 9-places

|                     |  |
|---------------------|--|
| Frame               | : steel chassis MIG welded with no-rust pre-treatment and powder-coating   |
| Towing hitch        | : 50 mm. ball-hitch coupling with additional safety-belt   |
| Loading platform    | : antiskid aluminium-plate   |
| Platform dimensions | : mm. 1236 x 2575  |
| Railing height      | : mm. 150 (front)  |
| Suspensions         | : link arms with progressive rubber springs  |
| Skis                | : steel made skis (3) with no-rust pre-treatment and powder-coating, equipped with HD-PE plastic skins and carbide wear-bars |
| Protections         | : triple R.O.P.S.  |
| Seats               | : removable 3+3+3 comfortable rubber-seats equipped with safety belts  |
| Available options   | : on request is available a kit including windshield and hard top and/or ski-rack 10-places                                  |
| Luggage rack        | : not available  |
| Weights             | : dry weight 265 kgs. / payload 753 kgs. / gross weight vehicle rating 1090 kgs.   |
| Capacities          | : 9 passengers / 753 kgs.  |

**Safety notes:** Transalp Bus 9 is designed to carry up to 9 persons. Partial loading of it must be shared between the front and the rear seats. Transalp Bus must be towed only by an Alpina snowmobile of the SHERPA or SUPERCLASS series equipped with the special ball hitch and safety strap. It is recommended to stud the snowmobile tracks to improve their grip on icy snow and also to install the emergency brake (EBS). The driver must have been trained in the specific use of the machine. Use by unexperienced people is absolutely prohibited. Operation is permitted only on groomed trails and not off-trail. The climbs and descents must be passed through the line of the maximum gradient and never transversally. The use of the Transalp Bus on trails where the slope and the snow conditions could compromise the stability and grip of the vehicle and constitute a danger for those being transported is forbidden. In this regard, it is recommended to not drive through the trails with gradients greater than 15% anyhow. Furthermore, circulation on roads open to public traffic or on ski slopes during the hours open to the public is prohibited (unless otherwise authorized). Max. speed permitted: 25 kph / 15 mph. Fasten safety belts before operating the snowmobile. It is recommended to provide insurance coverage for any damage that may be caused to driver and passengers, third parties and third party property (TPL).

