



Ski trail grooming equipment type F-250

Chassis	
frames	steel frame / MIG welded
towing bar	removable, suitable for pintle-hitch of SHERPA /SUPERCLASS series
coating	anti-oxidation pre-coating plus epoxy powder-coating finish
Grooming tool / first stage	
type	mechanical
tool specifications	3 rows / spring mounted 76 hard-steel knives
grooming width	mm. 1.800
grooming depth	electro-actuated
comb	PU finisher
combing width	mm. 2.500 (including end-flaps)
end-flaps	liftable end-flaps with ballast
Track-maker for Classic line (1st unit standard / 2nd unit* on request)	
tiller	12V DC electro-vibrating unit
pulse frequency	60 Hz.
tool features	16 hardened-steel knives
grooming width	420 mm.
grooming depth	45 mm.
trackshoes	UHMW polyethylene with progressive compacting profile
trackshoes distance	mm. 220
base	Pro-glide UHMW
track-maker width	540 mm.
additional side-plates	standard
track-maker lift-system	electro-actuated
track-maker pre-load	gas-springs
translator-system	mechanical
translator stroke	mm. 1.200 (corresponding to the center-to-center distance if equipped with 2 track-makers*)
electric system	12 V DC
controls	remote computer with “can-bus” system
wheeling-system	standard
estimated dry weight	235 kgs. with one track-maker / 280 kgs. with two track-makers*

The machine meets the 2004/108 and 2006/42 EEC norms.



